

MOTO TRANSMISIONES 10W40



MOTORCYCLE

Lubricants

Description

Lubricant oil formulated for lubricating motorcycle gearboxes. It provides excellent resistance to shearing and ensures that oil bath clutches operate with perfect slipping control in extreme conditions. It prolongs the life of all gearbox components, reduces mechanical noise and helps cold starts..

Properties

- Maximum protection against wear and extreme conditions for all parts of the gearbox.
- Provides optimum friction in clutch discs, preventing slippage.
- Enables speed and clutch changes to be carried out smoothly and precisely.

Quality Levels

- JASO T-903:2011 MA & MA2

Technical specifications

| | UNIT | METHOD | VALUE |
|-----------------------|-------------------|-------------|-----------|
| Density at 15 °C | g/cm ³ | ASTM D 4052 | 0.854 |
| Viscosity at 100 °C | cSt | ASTM D 445 | 14.1 |
| Viscosity at 40 °C | cSt | ASTM D 445 | 89 |
| Viscosity at -25 °C | cP | ASTM D 5293 | 7000 max. |
| Viscosity index | - | ASTM D 2270 | 160 |
| Flash point, open cup | °C | ASTM D 92 | 244 |
| Pour Point | °C | ASTM D 97 | -33 |
| T. B. N. | mg KOH/g | ASTM D 2896 | 7.7 |
| Sulphated ashes | % in weight | ASTM D 874 | 0.7 |

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 3 October 2014